

FSC-C032 Closure

Features

- ◇ Advanced internal structure design
- ◇ Easy to re-enter, it never requires re-entry kits
- ◇ Slide-in-lock design ,over 90° opening angle tray
- ◇ Earthing deriving device can be installed on the house of FOSC
- ◇ Elastic integrated seal fitting
- ◇ Operating Temperature : -40~+65 °C



www.youfibercable.com

Description

1. Three kinds of elastic ring provided: Ø21mm(minimum Ø13) 、 Ø15mm(minØ7) and Ø31mm(Ø23.5) or double hole Ø21mm.
2. The fittings provided with FSC-C032: 2pcs of special wrench, earthing wire, nylon tie, labeling paper, desiccant, 4 pieces of elastic ring,4 pieces of plastic gaskets.
3. Accessories for customers' selection: earthing deriving device, pressure testing valve, buffer tube for bunchy or ribbon fiber, 1 piece of special wrench, 1 piece metal hoop.

Parameter

Model	Size	Core capacity	Cable Ports	Max diameter of cable	Optical fiber splice tray(OFST) (Including heat shrinkable protective sleeve)
FSC-C031I (bunchy)	500x228 mm	144	4-5	1x31mm 3x21mm Or 2x21mm 3x21mm	OFST with 12 cores(1~12pcs of OFST 031)
FSC-C032II (bunchy)		192			OFST with 24cores(1~8pcs of OFST 032)
FSC-C040III (ribbon)		288			OFST with 72cores(1~4pcs of OFST 040)
FSC-C026IV (ribbon)		360			OFST with 72cores(1~5pcs of OFST 026)

Applications

- ◇ FTTB, FTTH (FTTx)
- ◇ ATM



FSC-C032 Closure

- ◇ CATV
- ◇ HFC