

FSC-C031 Closure

Features

- ◇ Advanced internal structure design
- ◇ Easy to re-enter, it never requires re-entry kits
- ◇ Slide-in-lock design ,over 90° opening angle tray
- ◇ Earthing deriving device can be installed on the house of FOSC
- ◇ Elastic integrated seal fitting
- ◇ Operating Temperature : -40~+65 °C



www.youfibercable.com

Description

1. 4 inlet/outlet ports provided: 4 ports suit for single fiber cable with max Ø16 and minimum Ø7mm. The inlet/outlet ports could be decided according to quantity and diameter of cable, the corresponding port plugs should be taken away.
2. The fittings provided with FSC-C031: 2pcs of special wrench, earthing wire, nylon tie, labeling paper, desiccant, 4pcs of elastic ring, 4pcs of plastic gaskets.
3. Accessories for customers' selection: earthing deriving device, pressure testing valve, buffer tube for bunchy fiber, 1 piece metal hoop.

Parameter

Model	Size	Core capacity	Cable Ports	Max diameter of cable	Optical fiber splice tray(OFST) (Including heat shrinkable protective sleeve)
FSC-C031I (bunchy)	415x190 mm	72	4	16mm	OFST with 12 cores(1~6pcs of OFST 031)
FSC-C032II (bunchy)		96			OFST with 24cores(1~4pcs of OFST 032)

Applications

- ◇ FTTB, FTTH (FTTx)
- ◇ ATM
- ◇ CATV
- ◇ HFC