

FSC-A018 Closure

Features

- ◇ Advanced internal structure design
- ◇ Easy to re-enter, it never requires re-entry kits
- ◇ Slide-in-lock design ,over 90° opening angle tray
- ◇ Earthing deriving device can be installed on the house of FOSC
- ◇ Elastic integrated seal fitting
- ◇ Operating Temperature : -40~+65 °C



www.youfibercable.com

Description

1. The installation accessories provided: seal tape, insulation tape, 3 pieces of special wrenches, hanging hook, abrasive cloth, earthing wire, nylon tie, labeling paper, measuring paper, desiccant.
2. Accessories for customers' selection: earthing deriving device, pressure testing valve, buffer tube for ribbon or bunchy fiber.

Parameter

Model	Size	Core capacity	Cable Ports	Max diameter of cable	Optical fiber splice tray(OFST) (Including heat shrinkable protective sleeve)
FSC-A018I (bunchy)	455x220x 132mm	96	6	2X23mm 2x20mm 2X16mm	OFST with 12 cores(1~8pcs of OFST 018)
FSC-A002II (bunchy)		144			OFST with 24cores(1~6pcs of OFST 002)
FSC-A004III (ribbon)		288			OFST with 72cores(1~4pcs of OFST 004)

Applications

- ◇ FTTB, FTTH (FTTx)
- ◇ ATM
- ◇ CATV
- ◇ HFC