

FSC-A023 Closure

Features

- ◇ Advanced internal structure design
- ◇ Easy to re-enter, it never requires re-entry kits
- ◇ Slide-in-lock design ,over 90° opening angle tray
- ◇ Earthing deriving device can be installed on the house of FOSC
- ◇ Elastic integrated seal fitting
- ◇ Operating Temperature : -40~+65 °C



www.youfibercable.com

Description

1. FSC-A023 provides one set of elastic seal fitting with 2x14mm inlet/outlet ports(if required, the sealing fittings with 4 x12 ports or 3 ports with 1 x14port and 2 x12 ports also provided). The necessary port plugs should be taken out.
2. The installation accessories: seal tape, insulation tape, 1piece of special wrenches, hanging hook, abrasive cloth, earthing wire, nylon tie, labeling paper, measuring paper, desiccant.
3. Accessories for customers' selection: buffer tube for bunchy fiber, aerial mounting bracket or wall mounting bracket.

Parameter

Model	Size	Core capacity	Cable Ports	Max diameter of cable	Optical fiber splice tray(OFST) (Including heat shrinkable protective sleeve)
FSC-A023I (bunchy)	280x200 mm	24~48	2	2X14mm Or 4X12mm	OFST with 6~12 cores(1~4pcs of OFST 022)
FSC-B037II (bunchy)		48~96			OFST with 12~24cores(1~4pcs of OFST 023)

Applications

- ◇ FTTB, FTTH (FTTx)
- ◇ ATM
- ◇ CATV
- ◇ HFC