

R401 SOHO Router

Features

- ♦ 5-Port Broadband Router
- ♦ Complies with IEEE 802.3, IEEE 802.3u standards
- \diamond Support firmware upgrade,
- ♦ Support Remote and Web management
- ♦ Support TCP/IP, PPPoE, DHCP, ICMP, NAT
- 10/100Mbps Auto-Negotiation WAN RJ45 port, supporting Auto-MDI/MDIX
- 10/100Mbps Auto-Negotiation LAN ports, supporting Auto-MDI/MDIX
- RADE BOULT IN THE REPORT
- Built-in NAT and DHCP server supporting static
 IP address distributing

- www.youfibercable.com
- ♦ Supports connecting/disconnecting Internet on a specified time of day
- ♦ Built-in Firewall supporting Domain Name filtering, and MAC address filtering
- ♦ Support Virtual Server, Special Application, and DMZ host
- Shares data and Internet access for Stations, connecting Internet through PPPoE on demand and disconnecting when idle

Description

The R401 Multifunctional Broadband Router is specially designed for small enterprise, office and SOHO(Small Office/Home Office) to access the Internet. It features strong functions, high performance, and easy configuration router. The R401 provides many management functions, including system, DHCP server, virtual server, DMZ host, firewall, and static routing table.

The R401 router provides flexible access control, limiting staff or children to browse selected sites. It connects to the Internet automatically or on demand and disconnects when idle to save on network costs. Quick Setup Wizard is supported and friendly help pages are provided for every step.

Parameter

Item	Description
Standard	IEEE 802.3、IEEE 802.3u、IEEE 802.3x
Protocol	CSMA/CA, CSMA/CD, TCP/IP, ICMP, NAT, PPPoE, DHCP, PPTP, UDP, NAT, DNS
SDRAM	1 M × 16 bits
Flash	4 M
Port type	LAN 4 10/100BaseTX (Auto MDI/MDIX) WAN 1 10/100BaseTX (Auto MDI/MDIX)
LED	1power, 1CPU status, 1WAN, 4LAN

E-mail: youfibercable@youfibercable.com MSN: youfiber@hotmail.com



R401 SOHO Router

www.youfibercable.com

Working rate	10/100Base-TX: UTP/STP CAT5e
Operating temperature	0°C~40°C
Storage temperature	-40°C ~70°C
Operating humidity	10%~90% RH no condensing
Storage humidity	5%~90% RH no condensing
Power supply	DC9V/AC100~240V
Dimension	178x120x30mm

Applications

 \diamond LAN

♦ SOHO Ethernet Network