


ASU aerial optical cable

Central Loose Tube Aerial Self Supportead,G.652D

Cable Design



Technical data

No. of cable		2~12
Fiber Model		G.652D
Loose Tube	Material	PBT
	Diameter	2.0 ± 0.1 mm
	Thickness	0.32 ± 0.05 mm
	Color	Nature
Strength Member	Material	FRP
	Diameter	2.0 ± 0.05 mm
Outer Sheath	Material	PE
	Color	Black
Cable Diameter		8.2 ± 0.2 mm
Cable Weight		60 ± 5.0 kg/km
Allowable Tensile Strength		1500N
Allowable Crush Resistance		2200N/100mm
Min. bending radius	Without Tension	$10.0 \times \text{Cable-} \phi$
	Under Maximum Tension	$20.0 \times \text{Cable-} \phi$
Temperature range (°C)	Installation	-20~+60
	Transport&Storage	-40~+70
	Operation	-40~+70

Fibre Color

No.	1	2	3	4	5	6
Color	Blue	Orange	Green	Brown	Gray	White
No.	7	8	9	10	11	12



Color	Red	Black	Yellow	Violet	Pink	Aqua
-------	-----	-------	--------	--------	------	------

The properties of single mode optical fiber (ITU-T Rec. G.652.D)

Item	Specification
Fiber type	Single mode
Fiber material	Doped silica
Attenuation coefficient	
@ 1310 nm	≤ 0.35 dB/km
@ 1383 nm	≤ 0.32 dB/km
@ 1550 nm	≤ 0.21 dB/km
@ 1625 nm	≤ 0.25 dB/km
Point discontinuity	≤ 0.05 dB
Cable cut-off wavelength	≤ 1260 nm
Zero-dispersion wavelength	1300 ~ 1324 nm
Zero-dispersion slope	≤ 0.092 ps/(nm ² .km)
Chromatic dispersion	
@ 1288 ~ 1339 nm	≤3.5 ps/(nm. km)
@ 1271 ~ 1360 nm	≤5.3 ps/(nm. km)
@ 1550 nm	≤18 ps/(nm. km)
@ 1625 nm	≤22 ps/(nm. km)
PMD _Q (Quadrature average*)	≤0.2 ps/km ^{1/2}
Mode field diameter @ 1310 nm	9.2±0.4 μm
Core / Clad concentricity error	≤ 0.5 μm
Cladding diameter	125.0 ± 0.7 μm
Cladding non-circularity	≤1.0%
Primary coating diameter	245 ± 10 μm
Proof test level	100 kpsi (=0.69 Gpa), 1%
Temperature dependence 0oC~ +70oC @ 1310 & 1550nm	≤ 0.1 dB/km

Main mechanical & environmental performance test

Item	Test Method	Acceptance Condition
Tensile Strength IEC 794-1-2-E1	- Load: 1500N - Length of cable: about 50m	- Fiber strain ≤ 0.33% - Loss change ≤ 0.1 dB @1550 nm - No fiber break and no sheath damage.
Crush Test IEC 60794-1-2-E3	- Load: 1000N/100mm - Load time: 1min	- Loss change ≤ 0.1dB@1550nm - No fiber break and no sheath damage.



Impact Test IEC 60794-1-2-E4	- Points of impact: 3 - Times of per point: 1 - Impact energy: 5J	- Loss change $\leq 0.1\text{dB}@1550\text{nm}$ - No fiber break and no sheath damage.
Temperature Cycling Test IEC60794-1-22-F1	- Temperature step: +20°C→-40°C→+70°C →+20°C - Time per each step: 12 hrs - Number of cycle: 2	- Loss change $\leq 0.1\text{ dB/km}@1550\text{ nm}$ - No fiber break and no sheath damage.

Sheath marking

The optical fiber drop cable shall have sequentially numbered length marking at intervals of approximately 1 meter. The starting number of ordering length for any coil shall begin with zero meter. The accuracy of the measurement of length marking shall be held within the limits of $\pm 1\%$.

- a) Manufacturer's name
- b) Type of wire
- c) Year and month of manufacture
- d) Length marking each meter along the wire