

## FSC-B010 Closure

### Features

- ◇ Advanced internal structure design
- ◇ Easy to re-enter, it never requires re-entry kits
- ◇ Slide-in-lock design ,over 90° opening angle tray
- ◇ Earthing deriving device can be installed on the house of FOSC
- ◇ Elastic integrated seal fitting
- ◇ Operating Temperature : -40~+65 °C



[www.youfibercable.com](http://www.youfibercable.com)

### Description

1. 4 inlet/outlet ports provided and the amount of heat shrinkable fixing sleeve is additionally ordered to the customers' actual need.
2. The fittings provided: 1pc wrench, aluminum-foil paper, earthing wire, nylon tie, labeling paper and desiccant.
3. Accessories for customers' selection: pressure testing valve, earthing deriving device, branching clip, heat shrinkable fixing sleeves, buffer tube for bunchy fiber and metal hoop.
4. It suits for straight-through fiber cable and branching fiber cable at the same time.

### Parameter

Model	Size	Core capacity	Cable Ports	Max diameter of cable	Optical fiber splice tray(OFST) (Including heat shrinkable protective sleeve)
FSC-B009I (bunchy)	410x190	48	4	3X16mm	OFST with 12 cores(1~4pcs of OFST 009)
FSC-B010II (bunchy)	mm	96		1X25mm	OFST with 24cores(1~4pcs of OFST 010)

### Applications

- ◇ FTTB, FTTH (FTTx)
- ◇ ATM
- ◇ CATV
- ◇ HFC