

FSC-B037 Closure

Features

- ◇ Advanced internal structure design
- ◇ Easy to re-enter, it never requires re-entry kits
- ◇ Slide-in-lock design ,over 90° opening angle tray
- ◇ Earthing deriving device can be installed on the house of FOSC
- ◇ Elastic integrated seal fitting
- ◇ Operating Temperature : -40~+65 °C



www.youfibercable.com

Description

1. 4 inlet/outlet ports provided and the amount of heat shrinkable fixing sleeve is additionally ordered to the customers' actual need.
2. The fittings provided: 1 piece of wrench, aluminum-foil paper, earthing wire, nylon tie, labeling paper and desiccant.
3. Accessories for customers' selection: pressure testing valve, earthing deriving device, branching clip, heat shrinkable fixing sleeves, buffer tube for bunchy fiber and metal hoop.

Parameter

Model	Size	Core capacity	Cable Ports	Max diameter of cable	Optical fiber splice tray(OFST) (Including heat shrinkable protective sleeve)
FSC-B036I (bunchy)	288x178	24	4	3X12mm	OFST with 12 cores(1~2pcs of OFST 036)
FSC-B037II (bunchy)	mm	48		1X13mm	OFST with 24cores(1~2pcs of OFST 037)

Applications

- ◇ FTTB, FTTH (FTTx)
- ◇ ATM
- ◇ CATV
- ◇ HFC